



Hazardous Decomposition or Byproducts: Decomposition may release oxides of sulfur, nitrogen, aldehydes, carbon monoxide, carbon dioxide and other low weight hydrocarbons.

---

**SECTION VI HEALTH HAZARD INFORMATION**

---

OSHA Exposure Limit	5 mg/m <sup>3</sup> (Mist); 10 mg/m <sup>3</sup> (Mist, Short Term).		
EYE CONTACT	Eye irritant.	SKIN CONTACT	Prolonged or repeated contact may cause mild irritation and possibly dermatitis. Prolonged or repeated contact with skin may result in allergic skin sensitization reactions.
INHALATION	High vapor/aerosol concentrations (at elevated temperatures) cause irritation, headache, dizziness, anesthesia, drowsiness, unconsciousness and death. Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection.	INGESTION	No significant adverse effects are expected upon ingestion of the product. If swallowed, can cause nausea, vomiting and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury, possibly death.

---

**SECTION VII EMERGENCY AND FIRST AID PROCEDURES**

---

EYE CONTACT	Flush with water for 15 minutes thoroughly. Get medical attention if irritation develops or persists.
SKIN CONTACT	Remove contaminated clothing. Wash with soap and water. Get medical attention if skin disorder develops. Launder contaminated clothing before reuse.
INHALATION	Remove to fresh air. If not breathing, give mouth-to-mouth resuscitation. Get medical attention if symptoms persist.
INGESTION	DO NOT INDUCE VOMITING. Consult local poison control center or get medical attention.

---

**SECTION VIII SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION	CONSUMER N/A	BULK HANDLING (Prolonged Exposure) If mist is generated (heating, spraying) and engineering control are not sufficient, wear approved organic vapor respirator suitable for oil mist.
VENTILATION	Use with adequate ventilation.	General.
EYE PROTECTION	N/A	Goggles or full-face shield.
PROTECTIVE CLOTHING	Use impervious gloves for prolonged contact.	Oil-impervious gloves and apron.

---

**SECTION IX PRECAUTIONS FOR SAFE HANDLING AND USE**

---

SPILL OR LEAK PROCEDURE	Remove all sources of ignition. Wear appropriate protective equipment and clothing during clean up. Do not allow the spilled product to enter public drainage systems or open water sources. Clean up area with absorbent material and place in closed container for disposal.
WASTE DISPOSAL METHOD	Dispose in accordance with all applicable local, state and federal regulations.
STORAGE AND HANDLING PRECAUTIONS	Store away from heat, sparks, open flame or strong oxidizing agents. Do not store this material in open or unlabeled containers. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose used containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. Avoid breathing mists and vapors, prolonged or repeated contact with this material. Avoid the generation of oil mists. Wash thoroughly after handling. Use this product with adequate ventilation.
OTHER PRECAUTIONS	Keep away from children and animals. Discharges or spills into or leading to surface waters that cause sheen must be reported to the National Response Center (1-800-424-8802).

---

**SECTION X                    OTHER INFORMATION**

---

**NFPA Hazard Rating**

- Health	1 Slight
- Fire	2 Moderate
- Reactivity	0 Least

---

Supersedes \_\_\_\_\_

OSHA Revised \_\_\_\_\_  
Title \_\_\_\_\_

*While Omni Specialty Packaging believes this data is accurate as of revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for your information, investigation, and verification.*